NOTICE

EFFECTIVE IMMEDIATELY:

FOOTING, FOUNDATION REBAR INSPECTIONS WILL BE REQUIRED ON ALL ONE-FAMILY AND TWO-FAMILY HOMES

Prior to submitting a Building Permit application, the applicant is required to submit (4) four sets of plans to the **Fire Department** for their review and approval stamp. One stamped set of plans will remain at the Fire Department, one stamped set will remain with the applicant, **TWO** stamped sets shall be submitted with the Building Permit application for the Building Inspector's notes, if any. When the permit is approved and the applicant comes in to pick it up, one of the stamped sets will be returned to the applicant and **that set is to stay on site for the Building Inspector to review during inspections.** Any addendums to the drawings through the course of the construction will need to be submitted for approval by the Fire Department and the Building Department.

A State approved septic design with Construction Approval must be submitted for new dwellings.

** Building permits are issued in two phases, Foundation Permit & Building Permit

<u>Foundation Permit</u>. After the permit is issued and after installation, inspections and final approval, the applicant will be required to submit the following 2 in order to obtain the 2nd phase Building Permit:

- a. Certified Plot Plan, stamped by a NH Licensed Land Surveyor, that shows the existing foundation with the setbacks to the property lines (does not need to show monuments set at this time).
- b. Sustained Yield Report from the well driller.

<u>Building Permit:</u> Once the 2 criteria above are received and deemed acceptable, and all permit and impact fees are paid, the building permit will be issued for the remainder of construction.

Prior to the issuance of a Certificate of Occupancy, a Certified Plot Plan showing monuments set is required, in addition to the items listed in this packet.



Town of Pelham 6 Village Green Pelham, NH 03076-3723 APPLICATION FOR BUILDING PERMIT

(603) 635-7811

1.	LOCATION OF Street Location BUILDING					
		Subdivision			Map	Lot
		☐ Convention	al Subdivision	Conservation Subdivision	Senior Hous	sing Project
2.	TYPE OF IMROVEME	NT 3.	PROPOSED USE			
	1 New Building 2 Foundation ONLY		Residential Single Family Two or more far # of units Garage Carport Shed		Deck Pool Wood/Pellet Stove Certificate of Occup Other (specify in se	
4.	ESTIMATED COST	5.	DESCRIPTION			
	1 Electrical \$					
	2 Plumbing \$					
	3 Mechanical \$					
	4 Other \$					
	Total Cost \$					
6.	PRINCIPAL TYPE OF FRAME 1	ring) 8.	Frontage Rear Setback WCD (Wetland Conser 1 Is the property locate 2 Is the proposed struct	d in a WCD area? ure located within the WCD in a special flood hazard are	Front Setback Right S Right S Ye area? Ye	etback
		10.	If yes, is the proposed structed located within the special flood hazard area: Yes No No No Has a variance required? Yes No Date of Hearing: Case #			— —
10	PRINCIPAL TYPE OF 1 Gas	HEATING FUE	L 11. DIME	NSIONS	12. NUMBER	OF OFF-STREET
Oil Coal Coal Cother – Specify			1 Number2 Total Liv3 Foundati	ring Area SF	_	d
13	. RESIDENTIAL BUILDI	NGS ONLY	1	14. Is the proposed wor		
	1 Total Bedrooms: Finish	ned1	Unfinished	Island, Gumpas, Long or Harris Ponds: Yes No		
2 Total Bathrooms: Full1/23/4		If yes, has approval been sought from NHDES? Yes No (Evidence of approved DES Shoreline Application OR written exemption by DES must be provided with this application)				

15. IDENTIFICATION NAME	MAILING ADDRESS	PHONE NUMBER
NAME	MAILING ADDRESS	PHONE NUMBER
1. Owner		
2. General		
Contractor		
3. Electrician**		
4. Plumber**		
SIGNATURE OF OWNER	APPLIC	ATION DATE:
**ELECTRICAL & PLU	MBING WORK REQUIRE SEPARATE PERMITS – THEY ARE NOT	
********	NOTE: CONSTRUCTION PLANS ARE NOT TO EXCEE ****PLANNING DEPARMTENT USE ONLY – DO NOT WRITE BEL	<mark>D 11"X 17"</mark> .OW THIS POINT*********************
Zoning/Planning Complian		
Zomig/Flammig Compilar	<u>ice</u>	
APPROVED		
Conditions of Approval to	be noted on Building Permit:	
-		
DENIED		
Reasons for Denial: See Al	DMINISTRATIVE DECISION DATED:	
Jenn Beauregard, Planner	/Zoning Administrator	Date
Jemi Deauregaru, Flamer	Zoning Administrator	Date
Review of Driveway Locat	ion:	
T ee C DI t Dt	 .	
Jeff Gowan, Planning Dire	ector	Date
Building Code Compliance	2	
APPROVED		
Conditions of Approval to	be noted on Building Permit:	
	To note on Sunting 1 transit	
		-
BUILDING PERMIT FEE:		
	spector	

New Hampshire Residential Energy Code Application

for Certification of Compliance for New Construction, Additions and/or Renovations of Detached One- and Two-family dwellings and multi-family dwellings (townhouses) not over 3 stories

EC-1 Form

Effective Date: September 15, 2019

Minimum Provisions from 2015 IRC Chapter 11

Owner/Owner Builder: Company Name: (if applicable) Name: Mail Address:			General Contractor: Company Name:			
			Name:			
			Mail Address:			
Town/City:	State:	Zip:	Town/City:	State:	Zip:	
Phone:	Cell:		Phone:	Cell:	<u> </u>	
E-Mail: Location of Proposed Structure: Tax Map #: Street: Town/City: County:			E-Mail: Type of Construction: O Residential O Small Commercial O New Building O Renovation O Thermally Isolated Sunroom O Modular Home: the site contractor must submit this form detailing supplementary rooms and Floor and/or Basement insulation unless the floor insulation is installed or provided by the manufacturer and no heated space is added.			
						Zone 5 Cheshir
Zone 6 All other NH counties and town of Durham		ft²				
			Basement or Ci space is one being heated a fixed opening into cond Conditioned? ○ Ye □ Full Basement □ Slab on Grade	d/cooled, containing uditioned space. Walls es (Walls must be in Walk Out)	ninsulated ducts or we must be insulated) sulated) O No Basement	
Structure is E	XEMPT because).• •	Form Submitted by:			
☐ Mobile Home	On an historic	register	Owner D Build	er		
specifications		y the local municipal of	and correct, and construction code official or New Hamps	hire Public Utilities C		
Official Use Only Date Complete Applie	cation Received:		Approved by:	Date:		
Approval Number:			Stamp:			

New Hampshire Energy Code EC-1

Certification No.:


Directions: Complete the "Your Proposed Structure" columns. No measurements or calculations are needed. Copies of plans are NOT needed. If you at least meet the Energy Code requirements, your project will be approved. Write N/A in any section that does not apply to your project. If your planned structure does meet these requirements, consider downloading REScheck http://www.energycodes.gov/rescheck to explore energy modelling options. **Please submit pages 1 and 2 only.**


YOUR PROPOSED STRUCTURE

			TOUR I ROI OSED STRUCTURE		
Building Section	Required R or U	Values	Write Planned R and U Values	Brands / Models / insulation type and thickness (if known)	
Window U Factor (lower U is better)	Factor U32 (if log walls in Zone 5) U30 (if log walls in Zone 6)		Write in U-Value	Check if Sunroom Log Walls	
Skylights	U .55 (or less	s)			
Flat Ceiling ⁱ or Flat Ceiling with Raised or Energy	6) if using the 6) if m		Write in R-Value → If using only R-	NOTE: R-38 will satisfy the requirement for R-49 if the full R-38 insulation value is maintained over the outside plates. If using only R-38 (Zone 5 or 6), you must certify that you will maintain R-38 over the plates by checking the box below. By checking this box, I certify that this structure is being built with a	
Trusses R-value	technique over the	ne plates if log walls	38 in Zone 5 or 6 you must check this box	raised energy truss or that the full R-value of the ceiling insulation will be maintained over the outside plates.	
Sloped or Cathedral Ceiling	Cathedral or 20% of total ceiling area or as above		Write in R-Value	Check if Sunroom	
Above Grade Wall ⁱⁱ R-value	Wall ⁱⁱ R-13 plus R-5		Write in R-Value	Log homes must comply with ICC400-2012, have an average minimum wall thickness of 5" or greater with specific gravity of ≤0.5 or 7" with specific gravity >0.5. Check if Sunroom Log Walls	
Door U-Value	U .32 (maximu	m)	Write in U-Value	One opaque door in the thermal envelope is exempt from the U-factor requirement.	
Floor R Value (Basement ceiling)	or Insulation sufficient to fill joist cavity		Write in R-Value	If conditioning the basement you must	
Basement or Crawl Space R-19 Cavity Insulation or R-15 Continuous Insulation		Write in R-Value	insulate Basement Walls . If not, you may insulate either Floor or Basement Walls and/or Slab Edge		
Slab Edge ⁱⁱⁱ R Value	R-10 2' (Zone 5) 4 (see drawing pg add R-5 if the Slab is hear under entire heated slab if	(3) ted or R-15	Write in R-Value	Check if Heated Slab	
A blower door test is required . The test must demonstrate an air exchange rate of <i>seven</i> Air Changes per Hour (ACH) or less @ 50 Pa.			If required by the code official, an approved third party may be required to conduct the blower door test.		

Footnotes to Residential Energy Code Application for Certification of Compliance

ⁱ <u>Ceilings with attic spaces</u>: R-38 in Zone 5 or 6 will be deemed to satisfy the requirement for R-49 wherever the full height of uncompressed R-38 insulation extends over the wall top plate at the eaves or the full R-value is maintained. This is often accomplished by using a raised heel or energy truss as shown in the diagram below or by using higher R-value insulation over the plates.






- ii R-13 + R-5 means R-13 cavity insulation plus R-5 continuous insulated sheathing. If structural sheathing covers 25 percent or less of the exterior, R-5 sheathing is not required where the structural sheathing is placed. If structural sheathing covers more than 25 percent of exterior, the structural sheathing must be supplemented with insulated sheathing of at least R-2.
- iii Slab edge insulation must start at the top of the slab edge and extend a total of two (Zone 5) or four feet (Zone 6). Insulation may go straight down, out at an angle away from the building, or along the slab edge and then under the slab. A slab is a concrete floor within 1' of grade level. See diagram below.

The top edge of insulation installed between the exterior wall and the interior slab may be mitered at a 45 degree angle away from the exterior wall.

Allowable Slab Insulation Configurations



A or A+ B must equal two feet in Zone 5 or four feet in Zone 6

MODULAR HOMES must be certified by the NH Department of Safety. Unless the floor insulation is provided by the manufacturer this form may be submitted. This form may also be submitted if the basement is to be insulated or supplementary heated space is added to the home upon or after it is set.

2015 2015 International Residential Code (IRC) effective Sept. 15, 2019 Residential Energy Code Requirements IRC Chapter 11

The following list is intended as a general summary of energy related requirements. Please consult the 2015 IRC Chapter 11 for complete requirements.

Certification No.:

Check here

	Air Leakage Code Section N1102.4	The building thermal envelope shall be constructed to limit air leakage in accordance with the requirements of IRC Sections R1102.4.1 through R1102.4.4. The building thermal envelope must be durably sealed to limit infiltration. See Table N1102.4.1.1 for a list of thermal envelope elements and installation criteria. Building envelope air tightness shall be verified to comply by Blower Door testing to no exceed air leakage of 7 Air Changes per Hour (ACH) at 50 Pascals pressure. The local Building Official may require an independent 3 rd party to conduct the test.			
	Testing Code Section N1102.4.1.2	The Blower Door Test is the required method to demonstrate code compliance with the air leakage requirement. Blower Door Test conducted by:			
	Fireplaces Code Section N1102.4.2	New wood-burning fireplaces shall have tight-fitting flue dampers or doors and outdoor combustion air.			
ľ	Recessed Lighting Code Section N1102.4.5	Recessed lights in the thermal envelope must be type IC rated and labeled as meeting ASTM E 283 and sealed with a gasket or caulk between the housing and the interior wall or ceiling covering.			
ľ	High-Efficacy Lighting	Not less than 75 percent of the lamps in permanenty installing lighting fixtures shall be high-			

Code Section N1104.1 efficacy lamps or not less than 75 percent of the permanently installed lighting fixtures shall contain only high-efficacy lamps. **Materials and Insulation** Materials, systems and equipment shall be identified in a manner that will allow a determination of code compliance. Manufacturer manuals for all installed heating, cooling and Identification service water heating equipment must be provided. Insulation R-values, glazing and door U-Code Section N1101.5 and values and heating and cooling equipment efficiency must be clearly marked on the building N1101.10 plans, drawings or specifications. **Pull-Down Attic Stairs**, Should be insulated to a level equal to the surrounding surfaces and tightly sealed and weather-Attic Hatch, and Knee stripped at the opening. **Wall Doors** Code Section N1102.2.4 All doors leading from a conditioned space into an unconditioned attic or enclosed attic or Full size Attic or **Basement Entry Doors** basement stairwell should be insulated and weather-stripped exterior rated door units meeting Code Section N1102.3.4 the U-factor requirement. One door is exempt.

Duct Insulation Code Section N1103.3.1	Supply and return ducts in attics must be insulated to at least R-8 where 3 in. diameter or greater. All other ducts must be insulated to at least R-6. Exception: Ducts or portions thereof located completely inside the building thermal envelope.	
Duct Construction Code Sections N1103.3.2 and N1103.3.5	Ducts, air handlers and filter boxes shall be sealed. Joints and seams must comply with the <i>In Mech. Code</i> or Section M1601.4.1 of the <i>International Residential Code</i> . Building framing cavities shall not be used as ducts or plenums (neither supply nor return).	
Duct Testing Code Sections 1103.3.3	Ducts shall be pressure tested to determine air leakage by either 1) rough-in test or 2) post-construction test. See Code for requirement details. Test conducted by: Duct test result at 25 Pa: Post construction or Rough-in test	
Temperature Controls Code Section N1103.1&1.1	At least one thermostat must be provided for each separate heating and cooling system. The thermostat controlling the primary system must be equipped with a programmable thermostat. Heat pumps having supplementary electric-resistance heat must have controls that, except during defrost, prevent supplemental heat operation when the heat pump compressor can meet the heating load	
Mechanical System Piping Insulation Code Section 1103.4	Mechanical system piping capable of conveying fluids at temperatures above 105°F or below 55°F must be insulated to R-3.	
Circulating Hot Water Systems Code Section N1103.5	Circulating service water systems must include an automatic or readily accessible manual switch that can turn off the hot water circulating pump when the system is not in use. Circulating domestic hot water system piping shall be insulated to R-4.	
Mechanical Ventilation Code Section N1103.6	Outdoor air intakes and exhausts must have automatic or gravity dampers that close when the ventilation system is not operating.	
Equipment Sizing Code Section N1103.7	Heating and cooling equipment shall be sized in accordance with ACCA Manual J or other approved heating and cooling calculation methodologies. Equipment shall have an efficiency rating equal to or greater than applicable federal standards.	
Certificate Code Section N1101.14	A permanent certificate, completed by the builder or registered design professional, must be posted on or in the electrical distribution panel. It must list the R-values of insulation installed in or on the ceiling, walls, foundation, and ducts outside the conditioned spaces; U-factors and SHGC for fenestration. The certificate must also list the type and efficiency of heating, cooling and service water heating equipment.	
Existing Buildings and Structures See Appendix J of IRC	The purpose of these provisions is to encourage continued use of existing buildings and structures. Work in existing buildings shall be classified into categories of repair, renovation, alteration and reconstruction. Consult this Appendix for specific requirements related to work in existing buildings.	



APPLICATION FOR DRIVEWAY PERMIT

Pursuant to the provisions of RSA 249:17 and the Subdivision Regulations of the Town of Pelham, New Hampshire, permission is requested to install a driveway entrance to my property at a location which will meet the requirements for safety specified in said statutes and regulations.

Proposed Location	:			
Tax Map Number of	Property:			
Street Name:		House #		
Number of nearest to	elephone pole:			
Side of Street:				
	(North, East, South, We	st)		
prior to cons	truction. afety Committee recommendation &	n showing the proposed location and designated prices. Fire Chief approval must be granted prices of Occupancy.		·
Driveway to Serve	Single Family Dwelling	Industry		Apartment
As the landowner ap	plicant, I hereby agree:			
1. To construct	the driveway entrance only for the bona	a fide purpose of securing access to private	e property :	such that

- the highway right-of-way is used for no purpose other than travel.
- 2. To construct the driveway entrance at the location determined by the Pelham Planning Board or its duly authorized agent to be the safest and according to the conditions imposed by the aforesaid statutes and regulations.
- 3. To furnish and install, at the applicants expense, drainage structures that are necessary to maintain existing highway drainage and adequately handle increased runoff resulting from present and future development.
- 4. To hold harmless the Pelham Planning Board and its duly authorized agents and employees against any action for personal injury and/or property damaged sustained by reason of the exercise of any driveway permit issued by the Pelham Planning Board or it's duly authorized agents and employees.

Conditions:

- 1. This permit requires the lot frontage area adjacent to the street be graded so that the elevation of the frontage, including driveway, will slope away from the edge of the street no less than a distance of 6 feet in width and not less than 6 inches in depth below the elevation of the edge of the street.
- 2. A culvert not less than 6 inches in diameter shall be installed under the driveway no less than 18 inches below the surface and in line with the drainage gutter referred to in Condition #1. The soil at each end of the culvert shall be stabilized by a header of adequate design.
- 3. The driveway entrance may be flared as it approaches the highway.

- 4. Other access to the highway from the premises is to be prevented by construction of a barrier or barriers, such as a grass plot, low hedge, curbed island, etc. The front face of this barrier shall be 25 feet from the centerline of the pavement.
- 5. The highway right-of-way line is located 25 feet from the parallel to the centerline of the highway.
- 6. No structures, including buildings, permanent or portable signs, lights, displays, fences, walls, sports equipment, sprinkler systems, etc. shall be permitted on, over, under or in the highway right-of-way.
- 7. No parking, catering or servicing shall be conducted within the highway right-of-way.

Final Approval:

- 8. No curbing shall be cut. Where there is curbing, the driveway shall be butted up against the curbing.
- 9. Failure (a) to adhere to the standards and engineering drawings, if any, previously submitted; (b) to adhere to the terms and conditions of the Driveway Permit Application: (c) to adhere to the terms of this permit; (d) to adhere to RSA 249:17 and the Driveway Permit Regulations of the Town of Pelham; and (e) to complete the driveway facility within one year, shall render this permit null and void.

•	'	
Signature of Landowner _		
Mailing Address		
-		
-		
ALL REQUESTS FOR DRI	IVEWAY INSPECTIONS SHOULD BE CALLED IN TO ONE WEEK FOR INSPECTION	
	DO NOT WRITE BELOW THIS LINE/ FOR OFFIC	CE USE ONLY
HIGHWAY SAFETY COMM	ITTEE INSPECTION/ COMMENTS	
Road Agent:		
☐ Planning Director:		
☐ Police Chief or Designe	ee:	
☐ Fire Chief or Designee:		

Fire Chief (NFPA Authority Having Jurisdiction)

The following driveway specifications are excerpted from the Town of Pelham Subdivision Regulations and are provided for your reference:

L. Driveways and Other Accesses for Single Family and Duplex lots

Driveways and other accesses to the local street network or proposed streets shall be constructed in accordance with the relevant provisions of the Pelham Subdivision Regulations, and the most recent version of the document entitled "State of New Hampshire Department of Transportation Policy and Procedure for Driveways and Other Accesses to the State Highway System". Driveways shall be defined in accordance with the definitions given in the most recent version of the Institute of Transportation Engineers Guidelines for Driveway Design and Location. Both of these documents are hereby incorporated into these regulations by reference. The more stringent requirements of the Pelham Subdivision regulations shall apply where different. The Planning Board shall retain approval authority for all wetland or WCD crossings or other lot access where steep slopes or other special features are present.

All driveways and other lot accesses shall be constructed as permitted then approved by the Fire Chief as the Authority Having Jurisdiction (AHJ) in accordance with NFPA I and in conjunction with Highway Safety Committee review and guidance prior to issuance of a building permit. The Fire Chief or his agent shall have jurisdiction for the design and location of all dry hydrants, fire cisterns or other water access.

A Special Permit will be required by the Planning Board before a driveway approved under these regulations is relocated with review and comment by the Highway Safety Committee and approval by the Fire Chief or his agent prior to the issuance of a building permit.

Driveway Specifications:

- 1. Driveways shall meet the roadway at a perpendicular angle and shall be flared 2 feet on each side where it meets the roadway. The driveway shall have a maximum slope of +/- 5% for the first 20 feet and any curves in the driveway shall have a minimum radius of 25' at the inside of the curve and 50' at the outside curb line.
- 2. Driveways of 150' or less in length shall be a minimum of 12' in width with a maximum slope of +/- 10% after the first 20' and the alignment shall permit a WB-50 Vehicle to pass (standard fire truck).
- 3. All driveways between 150' and 300' shall be a minimum of 14' in width with a maximum slope of +/- 10% after the first 20'.
- 4. All driveways exceeding 300' in length shall be a minimum of 14' in width after the first 20' with a maximum slope of +/- 10% and must be terminated with a paved turn-around area adequate for a WB/50 vehicle with a maximum slope of +/- 5% within the turn-around area.
- 5. All driveways 500' or more in length shall be a minimum of 14' in width, with a maximum slope of +/- 10% after the first 20' and shall include a pull over at the midpoint to accommodate a WB/50 vehicle allowing another WB/50 vehicle to safely pass. Driveways of this length shall be terminated with a paved turn-around area adequate for a WB/50 vehicle with a maximum slope of +/- 5% within the turn-around area.
- 6. All New subdivisions shall submit plans showing proposed driveways conforming to these minimum standards of this section in order to be approved.
- 7. Whenever a building permit is pulled the applicant shall submit a driveway application with a certified driveway plan that either conforms to the subdivision plan approved under these standards, or they must seek a special permit from the Planning Board and prove a new location of their choosing meets these minimum standards. Verification that the driveway complies with this section shall be made in writing by the Planning Board's review engineering firm.
- 8. All private driveways serving Senior and Elderly Housing projects shall be constructed to Town Road Specifications as defined within this document in addition to meeting all the requirements of the Fire Chief under NFPA I as described in this section.



WAIVER OF INTENT TO CUT WOOD OR TIMBER NOTICE

<u>Effective January 1, 1999</u> Pursuant to changes in RSA 79:1 II b Owners cutting for land conversion purposes are subject to the following condition:

- (b) The following persons **shall not** be required to file an intent to cut or be subject to the tax imposed by this Chapter:
 - (5) A person who cuts or causes to be cut, within the tax year, up to 10,000 board feet of logs and 20 cords of wood or the equivalent in whole tree chips, from the person's own land within a municipality, for land forest uses, provided that those persons intending to convert the use of the land have secured all required permits, including, but not limited to, building permits, subdivision or zoning permits, excavation permits or site plan approvals, as necessary for the use to which the land will be converted, and are able to furnish proof of such permits.

I,Cut for the property located	(Owner/Bu	uilder) do hereby certify that I have refused an Intent to
Cut for the property located	d at	
signing this form, I am cert RSA 79: 1 II (b) (2) (see all cutting operation before the appropriate notice of intent officials shall constitute a v post the certificate on the ju- I certify that I have read an	ifying that no standing ove) in preparation appropriate notice has been filed with iolation by the owner ob in a conspicuous dunderstand the ab	on the Pelham tax maps. I understand that by ng timber will be cut on this property except as defined in for building a house. I also understand that "starting a of intent has been filed with the Town and signed by the the Town and signed by the appropriate municipal er or any other person doing the cutting or both. Failure to a place upon receipt shall constitute a violation."
Office upon request.	id that I may receive	e any requested information form the remain Assessor's
		Owner / Builder
		Date
I certify that	there is no wood be	eing cut on this property
I certify that (wood being used for person	•	cut, but it is exempt per the above mentioned RSA

How to Obtain Permits to Install Oil or Gas Burning Equipment

- Applicant must fill out an application for permit to install oil burning equipment or gas burning equipment through the Fire Department.
- 2. Application fee is \$15.00 which is paid to the Fire Department.
- 3. The completed application will be held until the Fire Department is informed by the applicant that the burner is ready for inspection. At that time, an appointment will be made for the fire inspector to inspect the burner.
- 4. At the time of inspection, the fire inspector will also be checking your smoke alarms (hard-wired for new construction; battery operated for older homes), your battery operated or plug-in carbon monoxide detector alarms and making sure the number of your house is visible from the road.
- 5. Once inspected and approved, the applicant will be given (or mailed) a signed copy of the Permit,
- 6. Signed permit should be given to the Planning Department

Laws and regulations governing the installation of oil burners, gas burners, tanks, piping, etc. may be found in the National Fire Protection Association (NFPA) Standards and Town of Pelham guidelines.

If you have any further questions on the above procedures, please contact the Fire Department secretary at 635-2703, Monday thru Friday, 8:30 am to 4:30 pm.

PROPANE/OIL PERMITS AND INSPECTIONS

	PLANNING DEPARTMENT				
DEVICE	PLUMBING PERMIT	GAS PERMIT	ELECTRIC PERMIT	FIRE DEPT. PERMIT	
Propane Tank/Piping					
(Street Side of Regulator)				•	
Propane Tank/Piping					
(House Side of Regulator		•			
Oil Burner (Forced Hot Air)			•	•	
Oil Burner (Forced Hot Water)	•		•	•	
Propane (Forced Hot Air)		•	•	•	
Propane (Forced Hot Water)		•	•	•	
Oil Hot Water Heater	•		•	•	
Propane Hot Water Heater	•	•	•		
Propane Generator			•	•	
Gas/Diesel Generator			•	•	

PERMITS TO BE PULLED BEFORE ANY WORK IS INITIATED

This Policy Established On September 12, 2013 By Order Of The Pelham Fire Chief & Planning Director

James Midgley, Fire Chief

Jeff Goward Planning Director

***************	******	*******
** OCCUPANCY PERMIT	CHECKL	_IST**
LOCATION:	MAP:	LOT:
Any permit to occupy a residential or commercial building i	equires the	following:
1. Final Electrical Inspection		
2. Final Plumbing Inspection		
3. Final Building Inspection		
4. Final Driveway Inspection (Highway Safety Commit	tee 635-781	1) 🗌
The following information must accompany this form or be	on file at the	e Planning Dept.:
Certified Plot Plan showing location of building & mon	uments set	(granite bounds, iron pipes)
Copy of Septic As-Built Plan & Operation Approx Pollution Control Commission must accompany this for		ew Hampshire Water Supply and
Letter stating WCD Signs have been posted, if applica	ble.	
Oil/Gas Burning Permit (from the Fire Department 63	5-2703)	
Copy of Well Test to be done by a NH Certified Well the Board of Health Water Supply Regulations – Well C		b in accordance with Section 5 o
A completed Well Data Report submitted by the well d	riller or his a	agent.
A completed Blower Door Test . Must demonstrate an Hour (ACH) or less @ 50 Pa.	n air exchan	ige rate of seven Air Changes pe
☐ A COPY OF THE BUILDING PERMIT INCLUDING AL	L SIGNATU	JRES/DATES OF INSPECTIONS
All necessary approvals must be submitted to the Plant advance of requesting an occupancy permit. NO EXCEPT		ment at least 3 business days ir
I hereby certify that all the above approvals have bee accordance with above.	en submitte	d to the Planning Department in
Printed name of Builder/Owner:	Pł	none#
Signature of Builder/Owner:	Da	ate:

Please do not submit this with your application.

Keep this form to complete & submit at time of Certificate of Occupancy request.