

# **EFFECTIVE IMMEDIATELY:**

# FOOTING, FOUNDATION REBAR INSPECTIONS WILL BE REQUIRED ON ALL ONE-FAMILY AND TWO-FAMILY HOMES

Prior to submitting a Building Permit application, the applicant is required to submit (4) four sets of plans to the **Fire Department** for their review and approval stamp. One stamped set of plans will remain at the Fire Department, one stamped set will remain with the applicant, **TWO** stamped sets shall be submitted with the Building Permit application for the Building Inspector's notes, if any. When the permit is approved and the applicant comes in to pick it up, one of the stamped sets will be returned to the applicant and **that set is to stay on site for the Building Inspector to review during inspections.** Any addendums to the drawings through the course of the construction will need to be submitted for approval by the Fire Department and the Building Department.

A State approved septic design with Construction Approval must be submitted for new dwellings.

# \*\* Building permits are issued in two phases, Foundation Permit & Building Permit

<u>Foundation Permit</u>. After the permit is issued and after installation, inspections and final approval, the applicant will be required to submit the following in order to obtain the 2<sup>nd</sup> phase Building Permit:

- a. Certified Plot Plan, stamped by a NH Licensed Land Surveyor, that shows the existing foundation with the setbacks to the property lines (does not need to show monuments set at this time).
- b. Sustained Yield Report from the well driller.

<u>Building Permit:</u> Once the 2 criteria above are received and deemed acceptable, and all permit and impact fees are paid, the building permit will be issued for the remainder of construction.

Prior to the issuance of a Certificate of Occupancy, a Certified Plot Plan showing monuments set is required, in addition to the items listed in this packet.

	Town of Pelham 6 Village Green Pelham, NH 03076-3723 APPLICATION FOR BUILDING PERMIT (603) 635-7811				
1.	LOCATION OF BUILDING	Street Location			
		Subdivision	Мар	Lot	
		Conventional Subdivision Conser	vation Subdivision Sen	ior Housing Project	
2.	TYPE OF IMROVEME         1       New Building         2       Foundation ONLY	Residential		et Stove of Occupancy cify in section 5)	
4.	ESTIMATED COST	5. DESCRIPTION			
	1 Electrical       \$         2 Plumbing       \$         3 Mechanical       \$         4 Other       \$         Total Cost       \$				
6.	PRINCIPAL TYPE OF         FRAME         1       Masonry (wall beat         2       Wood frame         3       Structural steel         4       Reinforced concret         5       Other – Specify	<ul> <li>Frontage L Rear Setback</li> <li>8. WCD (Wetland Conservation 1 Is the property located in a V 2 Is the proposed structure loc</li> <li>9. Is the property located in a sp the Flood Insurance Rate Map If yes, is the proposed structed I</li> <li>10. Is a variance required? Ye Has a variance been approved?</li> </ul>			
10	PRINCIPAL TYPE OF 1           1         Gas           2         Oil           3         Electricity           4         Coal           5         Other – Specify	<ol> <li>Number of Stor</li> <li>Total Living Ar</li> </ol>	ea SF 2	UMBER OF OFF-STREET ARKING SPACES Enclosed Outdoors	
13		NGS ONLY         14.           ledUnfinished	Is the proposed work within 25 Island, Gumpas, Long or Harri If yes, has approval been sought to (Evidence of approved DES Shor exemption by DES must be provi	is Ponds:  Yes No from NHDES? Yes No reline Application OR written	

15. IDENTIFICATION						
	NAME	MAILING ADDRESS	PHONE NUMBER			
1. Owner						
2. General Contractor						
Contractor						
3. Electrician**						
4. Plumber**						
SIGNATURE OF	OWNER	APPLICATION DATI	F•			
SIGNATURE OF	OWNER	AIT LICATION DAT	B.			
**ELECTRI	CAL & PLUMBING WORK REQUIRE S	EPARATE PERMITS – THEY ARE NOT INCLUDED I	N THE BUILDING PERMIT**			
******	NOTE: CONSTR ********************PLANNING DEPARMT	RUCTION PLANS ARE NOT TO EXCEED 11"X 17" ENT USE ONLY – DO NOT WRITE BELOW THIS POI	NT********			
Zoning/Planning	<u>Compliance</u>					
APPROVED						
Conditions of Ap	proval to be noted on Building Pe	rmit:				
DENIED						
Decessor for Den	al Cas ADMINICTDATIVE DEC					
Reasons for Deni	al: <u>See ADMINISTRATIVE DEC</u>	USION DATED:				
Ionn Doounogond	Diannon/Zoning Administrator	Dete				
Jenn Beauregard, Planner/Zoning Administrator Date						
<b>Building Code C</b>	<u>ompliance</u>					
APPROVED						
Conditions of An	proval to be noted on Ruilding Pe	rmit:				
	Conditions of Approval to be noted on Building Permit:					
BUILDING PERMIT FEE:						
Roland Soucy, B	uilding Inspector	Date				

### New Hampshire Residential Energy Code Application

for Certification of Compliance for New Construction, Additions and/or Renovations of Detached One- and Two-family dwellings and multi-family dwellings (townhouses) not over 3 stories

EC-1 Form						
Minimum Provisions from 2015 IRC Chapter 11Effective Date: September 15, 2019						
<b>Owner/Owner Builder:</b> Company Name: (if applicable)			General Contr	General Contractor: Company Name:		
Name:			Name:			
Mail Address:			Mail Address:			
Town/City:	State:	Z <mark>ip:</mark>	Town/City:		State:	Zip:
Phone:	Cell:		Phone:		Cell:	
E-Mail:			<mark>E-Mail:</mark>		I	
Location of Proposed Structure:         Tax Map #:       Lot #:         Street:       Street:			<b>Type of Construction:</b> O ResidentialO Small CommercialO New BuildingO RenovationO AdditionO Thermally Isolated SunroomO Modular Home: the site contractor must submit this			
Town/City: County:		form detailing supplementary rooms and Floor and/or Basement insulation unless the floor insulation is installed or provided by the manufacturer and no heated space is added.				
Zone 5 O Cheshire, Hillsbo	orough, Rock	tingham Strafford	Total New Co	nditione	d* Floo	or Area:
<b>Zone 6</b> O All other NH counties and town of Durham			ft <sup>2</sup>			
			Basement or Crawl Space type:       (*a conditioned space is one being heated/cooled, containing uninsulated ducts or w/ a fixed opening into conditioned space. Walls must be insulated)         Conditioned?       O       Yes (Walls must be insulated)       O       No         Image: Full Basement       Image: Walk Out Basement       Image: Walk Out Basement       Image: Slab on Grade       O ther			
Structure is EXEMPT because:			Form Submitted by:			
☐ Mobile Home ☐ On an historic register		Owner Builder Other				

I hereby certify that all the information contained in this application is true and correct, and construction shall comply in all respects with the terms and specifications of the approval given by the local municipal code official or New Hampshire Public Utilities Commission.

Signature\_\_\_\_

Print Name

Date

Official Use Only	
Date Complete Application Received:	Approved by: Date:
Approval Number:	Stamp:

## **New Hampshire Energy Code EC-1**

**Certification No.:** 

YOUR PROPOSED STRUCTURE


Directions: Complete the "Your Proposed Structure" columns. No measurements or calculations are needed. Copies of plans are NOT needed. If you at least meet the Energy Code requirements, your project will be approved. Write N/A in any section that does not apply to your project. If your planned structure does meet these requirements, consider downloading REScheck http://www.energycodes.gov/rescheck to explore energy modelling options. Please submit pages 1 and 2 only.

		<b>I OUR I ROI OSED SIRUCIURE</b>		
Building Section	Required R or U Values	Write Planned R and U Values	Brands / Models / insulation type and thickness (if known)	
Window U Factor (lower U is better)	U .32 (maximum) U32 (if log walls in Zone 5) U30 (if log walls in Zone 6) U .50 (Thermally Isolated Sunrooms only)	Write in U-Value	Check if <b>Sunroom Log Walls</b>	
Skylights	<b>U</b> .55 (or less)			
Flat Ceiling <sup>i</sup> or Flat Ceiling with Raised or Energy Trusses R-value	Insulation <th>Write in R-Value</th> <th>NOTE: R-38 will satisfy the requirement for R-49 if the full R-38 insulation value is maintained over the outside plates. If using only R-38 (Zone 5 or 6), you must certify that you will maintain R-38 over the plates by checking the box below. By checking this box, I certify that this structure is being built with a raised energy truss or that the full R- value of the ceiling insulation will be maintained over the outside plates.</th>	Write in R-Value	NOTE: R-38 will satisfy the requirement for R-49 if the full R-38 insulation value is maintained over the outside plates. If using only R-38 (Zone 5 or 6), you must certify that you will maintain R-38 over the plates by checking the box below. By checking this box, I certify that this structure is being built with a raised energy truss or that the full R- value of the ceiling insulation will be maintained over the outside plates.	
Sloped or Cathedral Ceiling	<ul> <li>R-30 (Zone 5 &amp; 6) if less than 500 ft sq or 20% of total ceiling area or as above</li> <li>R-24 (Thermally Isolated Sunrooms only)</li> </ul>	Write in R-Value	Check if D Sunroom	
Above Grade Wall <sup>ii</sup> R-value	R-20 Cavity Insulation only <i>or</i> R-13 <i>plus</i> R-5 Cavity <i>plus</i> Continuous Insulation R-13 (Thermally Isolated Sunrooms only)	Write in R-Value	Log homes must comply with ICC400-2012, have an average minimum wall thickness of 5" or greater with specific gravity of ≤0.5 or 7" with specific gravity >0.5. Check if □ Sunroom □ Log Walls	
Door U-Value	<b>U</b> .32 (maximum)	Write in U-Value	One opaque door in the thermal envelope is exempt from the U-factor requirement.	
Floor R Value (Basement ceiling)R-30 or Insulation sufficient to fill joist cavity		Write in R-Value	If conditioning the basement you must	
Basement or Crawl Space Wall R ValueFor both Zone 5 and Zone 6 R-19 Cavity Insulation or R-15 Continuous Insulation		Write in R-Value	insulate <b>Basement Walls</b> . If not, you may insulate either <b>Floor</b> or <b>Basement Walls</b> and/or <b>Slab Edge</b>	
Slab Edge <sup>iii</sup> R Value	R-10 2' (Zone 5) 4' (Zone 6) (see drawing pg 3) add R-5 if the Slab is heated or R-15 under entire heated slab if a log home.	Write in R-Value	Check if <b>Heated Slab</b>	
Air SealingA blower door test is required. The test must demonstrate an air exchange rate of seven Air Changes per Hour (ACH) or less @ 50 Pa.			If required by the code official, an approved third party may be required to conduct the blower door test.	

Submit pages 1 and 2 to local municipal code official or NH Public Utilities Commission at <u>energycodes@puc.nh.gov</u> Phone: 603.271.2431. Fax: 603.271.3878.

### Footnotes to Residential Energy Code Application for Certification of Compliance


<sup>i</sup> <u>Ceilings with attic spaces</u>: R-38 in Zone 5 or 6 will be deemed to satisfy the requirement for R-49 wherever the full height of uncompressed R-38 insulation extends over the wall top plate at the eaves or the full R-value is maintained. This is often accomplished by using a raised heel or energy truss as shown in the diagram below or by using higher R-value insulation over the plates.



<sup>ii</sup> R-13 + R-5 means R-13 cavity insulation plus R-5 continuous insulated sheathing. If structural sheathing covers 25 percent or less of the exterior, R-5 sheathing is not required where the structural sheathing is placed. If structural sheathing covers more than 25 percent of exterior, the structural sheathing must be supplemented with insulated sheathing of at least R-2.

<sup>iii</sup> Slab edge insulation must start at the top of the slab edge and extend a total of two (Zone 5) or four feet (Zone 6). Insulation may go straight down, out at an angle away from the building, or along the slab edge and then under the slab. A slab is a concrete floor within 1' of grade level. See diagram below.

The top edge of insulation installed between the exterior wall and the interior slab may be mitered at a 45 degree angle away from the exterior wall.



### Allowable Slab Insulation Configurations

A or A+ B must equal two feet in Zone 5 or four feet in Zone 6

MODULAR HOMES must be certified by the NH Department of Safety. Unless the floor insulation is provided by the manufacturer this form may be submitted. This form may also be submitted if the basement is to be insulated or supplementary heated space is added to the home upon or after it is set.

### 2015 International Residential Code (IRC) effective Sept. 15, 2019 Residential Energy Code Requirements IRC Chapter 11 The following list is intended as a general summary of energy related requirements. Please consult the 2015 IRC Chapter 11 for complete requirements.

eck here	Certification No.:
<b>Air Leakage</b> Code Section N1102.4	The building thermal envelope shall be constructed to limit air leakage in accordance with the requirements of IRC Sections R1102.4.1 through R1102.4.4. The building thermal envelope must be durably sealed to limit infiltration. See Table N1102.4.1.1 for a list of thermal envelope elements and installation criteria.
	Building envelope air tightness shall be verified to comply by Blower Door testing to no exceed air leakage of 7 Air Changes per Hour (ACH) at 50 Pascals pressure. The local Building Official may require an independent 3 <sup>rd</sup> party to conduct the test.
T. d	The Blower Door Test is the required method to demonstrate code compliance with the air leakage requirement.
Testing	Blower Door Test conducted by:
Code Section N1102.4.1.2	Result (at 50 Pa):CFM Interior VolumeCFACH
<b>Fireplaces</b> Code Section N1102.4.2	New wood-burning fireplaces shall have tight-fitting flue dampers or doors and outdoor combustion air.
<b>Recessed Lighting</b> Code Section N1102.4.5	Recessed lights in the thermal envelope must be type IC rated and labeled as meeting ASTM 283 and sealed with a gasket or caulk between the housing and the interior wall or ceiling covering.
High-Efficacy Lighting Code Section N1104.1	Not less than 75 percent of the lamps in permanenty installing lighting fixtures shall be high efficacy lamps or not less than 75 percent of the permanently installed lighting fixtures shal contain only high-efficacy lamps.
Materials and Insulation Identification Code Section N1101.5 and N1101.10	Materials, systems and equipment shall be identified in a manner that will allow a determination of code compliance. Manufacturer manuals for all installed heating, cooling ar service water heating equipment must be provided. Insulation R-values, glazing and door U-values and heating and cooling equipment efficiency must be clearly marked on the building plans, drawings or specifications.
Pull-Down Attic Stairs, Attic Hatch, and Knee Wall Doors	Should be insulated to a level equal to the surrounding surfaces and tightly sealed and weathe stripped at the opening.
Code Section N1102.2.4	
Full size Attic or Basement Entry Doors Code Section N1102.3.4	All doors leading from a conditioned space into an unconditioned attic or enclosed attic or basement stairwell should be insulated and weather-stripped exterior rated door units meeting the U-factor requirement. One door is exempt.

<b>Duct Insulation</b> Code Section N1103.3.1	<b>Supply and return</b> ducts in attics must be insulated to at least R-8 where 3 in. diameter or greater. All other ducts must be insulated to at least R-6. Exception: Ducts or portions thereof located completely inside the building thermal envelope.	
Duct Construction Code Sections N1103.3.2 and N1103.3.5	Ducts, air handlers and filter boxes shall be sealed. Joints and seams must comply with the <i>Int. Mech. Code</i> or Section M1601.4.1 of the <i>International Residential Code</i> . Building framing cavities <b>shall not</b> be used as ducts or plenums (neither supply nor return).	
<b>Duct Testing</b> Code Sections 1103.3.3	Ducts shall be pressure tested to determine air leakage by either 1) rough-in test or 2) post-construction test. See Code for requirement details.         Test conducted by:         Duct test result at 25 Pa:         Post construction or         Rough-in test	
<b>Temperature Controls</b> Code Section N1103.1&1.1	At least one thermostat must be provided for each separate heating and cooling system. The thermostat controlling the primary system must be equipped with a programmable thermostat. Heat pumps having supplementary electric-resistance heat must have controls that, except during defrost, prevent supplemental heat operation when the heat pump compressor can meet the heating load	
Mechanical System Piping Insulation Code Section 1103.4	Mechanical system piping capable of conveying fluids at temperatures above 105°F or below 55°F must be insulated to R-3.	
Circulating Hot Water Systems Code Section N1103.5	Circulating service water systems must include an automatic or readily accessible manual switch that can turn off the hot water circulating pump when the system is not in use. Circulating domestic hot water system piping shall be insulated to R-4.	
Mechanical Ventilation Code Section N1103.6	Outdoor air intakes and exhausts must have automatic or gravity dampers that close when the ventilation system is not operating.	
Equipment Sizing Code Section N1103.7	Heating and cooling equipment shall be sized in accordance with ACCA Manual J or other approved heating and cooling calculation methodologies. Equipment shall have an efficiency rating equal to or greater than applicable federal standards.	
<b>Certificate</b> Code Section N1101.14	A permanent certificate, completed by the builder or registered design professional, must be posted on or in the electrical distribution panel. It must list the R-values of insulation installed in or on the ceiling, walls, foundation, and ducts outside the conditioned spaces; U-factors and SHGC for fenestration. The certificate must also list the type and efficiency of heating, cooling and service water heating equipment.	
Existing Buildings and Structures See Appendix J of IRC	The purpose of these provisions is to encourage continued use of existing buildings and structures. Work in existing buildings shall be classified into categories of repair, renovation, alteration and reconstruction. Consult this Appendix for specific requirements related to work in existing buildings.	

NEW HAMPSHIRE ENERGY CODE Summary of Basic Requirements Page 2



### APPLICATION FOR DRIVEWAY PERMIT

Pursuant to the provisions of RSA 249:17, RSA 236:13 and the Subdivision Regulations of the Town of Pelham, New Hampshire, permission is requested to install a driveway entrance to my property at a location which will meet the requirements for safety specified in said statutes and regulations.

# Attention: The Planning Department and The Highway Department must be provided a plan showing the proposed location and design of the driveway prior to inspections or construction.

### **Proposed Location:**

Tax Map Number of Property:					
Street Name:		House #			
Side of Street:					
	(North, East, South, West)				
Driveway to Serve	Single Family Dwelling	Industry Apartment House Subdivision			

As the landowner applicant, I hereby agree:

- 1. To construct the driveway entrance only for the bona fide purpose of securing access to private property such that the roadway right-of-way is used for no purpose other than travel.
- 2. To construct the driveway entrance at the location determined by the Pelham Planning Board or its duly authorized agent to be the safest and according to the conditions imposed by the aforesaid statutes and regulations.
- 3. To furnish and install, at the applicants' expense, drainage structures that are necessary to maintain existing roadway drainage and adequately handle increased runoff resulting from present and future development.
- 4. To hold harmless the Pelham Planning Board and its duly authorized agents and employees against any action for personal injury and/or property damaged sustained by reason of the exercise of any driveway permit issued by the Pelham Planning Board or it's duly authorized agents and employees.

### **Conditions:**

- 1. This permit requires the lot frontage area adjacent to the street be graded so that the elevation of the frontage, including driveway, will slope away from the edge of the street no less than 6 feet in width and not less than 6 inches in depth below the elevation of the edge of the street.
- 2. A copy of the plans with the proposed driveway and elevation of driveway apron is to be submitted to both the Planning Department and the Highway Department with the Driveway Permit Application.
- 3. Each driveway is to have no less than two inspections; a preliminary inspection of the unpaved driveway once it is staked out, and then a final inspection of the finished paved driveway.
- 4. Driveways must have at minimum, 250-feet of all-season safe sight distance when intersecting a Local-1 or Local-2 Street; and 325-feet if intersecting a Collector Street.
- 5. All residential driveways are to intersect the roadway at a ninety-degree angle with an apron no smaller than 14-feet wide and no larger than twenty-feet wide with a negative slope of at-least 2% and at most 3% which is to be maintained for no-less than ten-feet from the edge of roadway. At that point the slope can change, but with an algebraic difference of no more than 10%.

- 6. A culvert not less than 6 inches in diameter shall be installed under the driveway no less than 18 inches below the surface and in line with the drainage gutter referred to in Condition #1. The soil at each end of the culvert shall be stabilized by a header of adequate design.
- 7. The driveway entrance may be flared as it approaches the roadway.
- 8. Other access to the roadway from the premises is to be prevented by construction of a barrier or barriers, such as a grass plot, low hedge, curbed island, etc. The front face of this barrier shall be no-less-than 25 feet from the centerline of the pavement.
- 9. The roadway right-of-way line is typically found 25-feet from the parallel to the centerline but should be verified.
- 10. No structures, including buildings, permanent or portable signs, lights, displays, fences, walls, sports equipment, sprinkler systems, etc. shall be permitted on, over, under or in the right-of-way.
- 11. No parking, catering or servicing shall be conducted within the right-of-way.
- 12. No curbing shall be cut. Where there is curbing, the driveway shall be butted up against the curbing.
- 13. Failure (a) to adhere to the standards and engineering drawings, if any, previously submitted; (b) to adhere to the terms and conditions of the Driveway Permit Application: (c) to adhere to the terms of this permit; (d) to adhere to RSA 249:17 and the Driveway Permit Regulations of the Town of Pelham; and (e) to complete the driveway facility within one year, shall render this permit null and void.

# The Highway Safety Committee recommendation & Fire Chief approval must be granted prior to issuance of Certificate of Occupancy.

Printed Name of Landowner

Signature of Landowner

Owners Phone Number

Mailing Address

# ALL REQUESTS FOR DRIVEWAY INSPECTIONS SHOULD BE CALLED IN TO 603-635-7811 EXT.4. PLEASE ALLOW UP TO ONE WEEK FOR EACH INSPECTION.

### **\*\*DO NOT WRITE BELOW THIS LINE. FOR OFFICE USE ONLY\*\***

<b>DRIVEWAY APPROVED</b>	<b>DRIVEWAY DENIED</b>
If Driveway denied, why?	
Road Agent:	
Highway Dept:	
Planning Dept:	

**Final Approval:** 

The following driveway specifications are excerpted from the Town of Pelham Subdivision Regulations and are provided for your reference, Appendix 1 – Roadway Design, Section L, as follows:

#### L. Driveways and Other Accesses for Single Family and Duplex lots

Driveways and other accesses to the local street network or proposed streets shall be constructed in accordance with the relevant provisions of the Pelham Subdivision Regulations, and the most recent version of the document entitled "State of New Hampshire Department of Transportation Policy and Procedure for Driveways and Other Accesses to the State Highway System". Driveways shall be defined in accordance with the definitions given in the most recent version of the Institute of Transportation Engineers Guidelines for Driveway Design and Location. Both of these documents are hereby incorporated into these regulations by reference. The more stringent requirements of the Pelham Subdivision regulations shall apply where different. The Planning Board shall retain approval authority for all wetland or WCD crossings or other lot access where steep slopes or other special features are present.

All driveways and other lot accesses shall be constructed as permitted then approved by the Fire Chief as the Authority Having Jurisdiction (AHJ) in accordance with NFPA I and in conjunction with Highway Safety Committee review and guidance prior to issuance of a building permit. The Fire Chief or his agent shall have jurisdiction for the design and location of all dry hydrants, fire cisterns or other water access.

A Special Permit will be required by the Planning Board before a driveway approved under these regulations is relocated with review and comment by the Highway Safety Committee and approval by the Fire Chief or his agent prior to the issuance of a building permit.

#### **Driveway Specifications:**

- 1. Driveways shall meet the roadway at a perpendicular angle and shall be flared 2 feet on each side where it meets the roadway. The driveway shall have a maximum slope of +/- 5% for the first 20 feet and any curves in the driveway shall have a minimum radius of 25' at the inside of the curve and 50' at the outside curb line.
- 2. Driveways of 150' or less in length shall be a minimum of 12' in width with a maximum slope of +/- 10% after the first 20' and the alignment shall permit a WB-50 Vehicle to pass (standard fire truck).
- 3. All driveways between 150' and 300' shall be a minimum of 14' in width with a maximum slope of +/-10% after the first 20'.
- 4. All driveways exceeding 300' in length shall be a minimum of 14' in width after the first 20' with a maximum slope of +/- 10% and must be terminated with a paved turn-around area adequate for a WB/50 vehicle with a maximum slope of +/- 5% within the turn-around area.
- 5. All driveways 500' or more in length shall be a minimum of 14' in width, with a maximum slope of +/- 10% after the first 20' and shall include a pull over at the midpoint to accommodate a WB/50 vehicle allowing another WB/50 vehicle to safely pass. Driveways of this length shall be terminated with a paved turn-around area adequate for a WB/50 vehicle with a maximum slope of +/- 5% within the turn-around area.
- 6. All New subdivisions shall submit plans showing proposed driveways conforming to these minimum standards of this section in order to be approved.
- 7. Whenever a building permit is pulled the applicant shall submit a driveway application with a certified driveway plan that either conforms to the subdivision plan approved under these standards, or they must seek a special permit from the Planning Board and prove a new location of their choosing meets these minimum standards. Verification that the driveway complies with this section shall be made in writing by the Planning Board's review engineering firm.
- 8. All private driveways serving Senior and Elderly Housing projects shall be constructed to Town Road Specifications as defined within this document in addition to meeting all the requirements of the Fire Chief under NFPA I as described in this section.



# WAIVER OF INTENT TO CUT WOOD OR TIMBER NOTICE

<u>Effective January 1, 1999</u> Pursuant to changes in RSA 79:1 II b Owners cutting for land conversion purposes are subject to the following condition:

(b) The following persons **shall not** be required to file an intent to cut or be subject to the tax imposed by this Chapter:

(5) A person who cuts or causes to be cut, within the tax year, up to 10,000 board feet of logs and 20 cords of wood or the equivalent in whole tree chips, from the person's own land within a municipality, for land forest uses, provided that those persons intending to convert the use of the land have secured all required permits, including, but not limited to, building permits, subdivision or zoning permits, excavation permits or site plan approvals, as necessary for the use to which the land will be converted, and are able to furnish proof of such permits.

l,	_ (Owner/Builder) do hereby certify that I have refused an Intent to
Cut for the property located at	

(address)

also known as Map \_\_\_\_\_\_ Lot \_\_\_\_\_ on the Pelham tax maps. I understand that by signing this form, I am certifying that no standing timber will be cut on this property except as defined in RSA 79: 1 II (b) (2) (see above) in preparation for building a house. I also understand that "starting a cutting operation before the appropriate notice of intent has been filed with the Town and signed by the appropriate notice of intent has been filed with the Town and signed by the appropriate municipal officials shall constitute a violation by the owner or any other person doing the cutting or both. Failure to post the certificate on the job in a conspicuous place upon receipt shall constitute a violation."

I certify that I have read and understand the above form. If I need further information concerning Intent to Cut Statutes, I understand that I may receive any requested information form the Pelham Assessor's Office upon request.

Owner / Builder

Date

\_\_\_\_\_I certify that there is no wood being cut on this property

\_\_\_\_\_ I certify that there is wood being cut, but it is exempt per the above mentioned RSA (wood being used for personal use).

# How to Obtain Permits to Install Oil or Gas Burning Equipment

- 1. Applicant must fill out an application for permit to install oil burning equipment **or** gas burning equipment through the Fire Department.
- 2. Application fee is \$15.00 which is paid to the Fire Department.
- 3. The completed application will be held until the Fire Department is informed by the applicant that the burner is ready for inspection. At that time, an appointment will be made for the fire inspector to inspect the burner.
- 4. At the time of inspection, the fire inspector will also be checking your smoke alarms (hard-wired for new construction; battery operated for older homes), your battery operated or plug-in carbon monoxide detector alarms and making sure the number of your house is visible from the road.
- 5. Once inspected and approved, the applicant will be given (or mailed) a signed copy of the Permit,
- 6. Signed permit should be given to the Planning Department

Laws and regulations governing the installation of oil burners, gas burners, tanks, piping, etc. may be found in the National Fire Protection Association (NFPA) Standards and Town of Pelham guidelines.

If you have any further questions on the above procedures, please contact the Fire Department secretary at 635-2703, Monday thru Friday, 8:30 am to 4:30 pm.

#### PLANNING DEPARTMENT FIRE DEPARTMENT DEVICE PLUMBING PERMIT GAS PERMIT ELECTRIC PERMIT FIRE DEPT. PERMIT Propane Tank/Piping (Street Side of Regulator) • Propane Tank/Piping (House Side of Regulator • Oil Burner (Forced Hot Air) • • • • • Oil Burner (Forced Hot Water) • • Propane (Forced Hot Air) • • • • Propane (Forced Hot Water) Oil Hot Water Heater • • • • • • Propane Hot Water Heater Propane Generator • • • Gas/Diesel Generator •

#### **PROPANE/OIL PERMITS AND INSPECTIONS**

#### **\*\*PERMITS TO BE PULLED BEFORE ANY WORK IS INITIATED\*\***

This Policy Established On September 12, 2013 By Order Of The Pelham Fire Chief & Planning Director

James Midgley, Fire Chief

Jeff Gowar, Planning Director

# **\*\* OCCUPANCY PERMIT CHECKLIST\*\***

LOCATION:	MAP:	LOT:
Any permit to occupy a residential or commercial bui	Iding requires the	following:
1. Final Electrical Inspection		
2. Final Plumbing Inspection		
3. Final Building Inspection		
4. Final Driveway Inspection (Highway Safety Co	ommittee 635-781	1)
The following information must accompany this form	or be on file at the	e Planning Dept.:
Certified Plot Plan showing location of building &	& monuments set	(granite bounds, iron pipes)
Copy of Septic As-Built Plan & Operation A Pollution Control Commission must accompany the		ew Hampshire Water Supply and
Letter stating <b>WCD Signs</b> have been posted, if a	pplicable.	
Oil/Gas Burning Permit (from the Fire Departme	ent 635-2703)	
Copy of <b>Well Test</b> to be done by a <b>NH Certified</b> the Board of Health Water Supply Regulations –	-	<b>b</b> in accordance with Section 5 of
A completed Well Data Report submitted by the	well driller or his a	agent.
A completed <b>Blower Door Test</b> . Must demonstr Hour (ACH) or less @ 50 Pa.	ate an air exchan	ge rate of seven Air Changes per
A COPY OF THE BUILDING PERMIT INCLUDIN	NG ALL SIGNATU	JRES/DATES OF INSPECTIONS
All necessary approvals <b>must be submitted</b> to the <b>advance</b> of requesting an occupancy permit. <b>NO EX</b>		ment at least 3 business days in
I hereby certify that all the above approvals hav accordance with above.	e been submitted	d to the Planning Department in
Printed name of Builder/Owner:	Pr	none#
Signature of Builder/Owner:	Da	ate:
*****		
Please do not submit thi	is with your ap	plication.

Keep this form to complete & submit at time of Certificate of Occupancy request.